

www.otterbine.com/led

## + Energy Efficient

- 80% Energy Savings Over Traditional MR16 Halogen Lamps
- Low Voltage 6.5W LED Light Pulls Less Than 0.1 Amps

## + Versatile


- 2, 4, 6 and 8-light Configurations to Complement Units from 1/2HP to 10HP
- Bright White (5700K) or Warm White (3000K) Lamps Available

## + Cost Effective


 Integrating DC Power Supply Allows for Cleaner Power and Longer Cable Runs with Smaller Gauge Cable

### + Convenient

 All LED Light Systems for 1HP-10HP & Fractional Deluxe Units Come Standard with Cable Quick Disconnect



DC Power Supply is Mounted in the Power Control Center and Replaces the Traditional Transformer/ Junction Box Found in Most Light Systems.



Distribution Box Mounted to Side of Unit Allowing for Shallower Operating Depths on Concept 3 Units

LED LIGHT MAXIMUM CABLE LENGTHS						
Lights per	16AWG / 1.5mm²		12AWG / 4mm²			
Set	Feet	Meters	Feet	Meters		
2*	150	46	300	91		
2	650	198	1000	305		
4	325	99	700	213		
6	225	69	525	160		
8**	325	99	700	213		

<sup>\*</sup> Used on 1/2HP & 3/4HP Units. \*\*8-light set requires two cable runs. Contact factory for longer cable runs.

www.otterbine.com/led

# FOUNTAIN GLO™ LIGHT SYSTEMS

Manufactured by: Otterbine® Barebo, Inc. | 3840 Main Road East | Emmaus, PA 18049 U.S.A | PH: 610-965-6018

### MR16 LED LIGHT SYSTEMS




Otterbine LED low voltage light systems come with an energy efficient 6.5W bulb that is available in a bright white (5700K) or warm white (3000K) flood lamp. System operates off 115V in 60Hz, and 220V in 50Hz; options include photocell and colored lenses. Manufactured from corrosion resistant thermal plastics our LED light systems come in 2, 4, 6 and 8-light configurations.

Recommended for all 1HP through 10HP aeration and fountain systems, these systems comply with UL1838 and are CE listed.

Lights (6.5W LED)	2*	2	4	6	8**
Amp Draw	.15	.18	.35	.53	.70
Output Electrical Rating	12VDC	15VDC	15VDC	15VDC	15VDC
Lamp Wattage (Total)	13	13	26	39	52

Lamp Options	2	4	6	8**
Bright White (Lumens)	970	1,940	2,910	3,880
Warm White (Lumens)	700	1,400	2,100	2,800



\*Used on 1/2HP & 3/4HP units. \*\*Requires two cable runs. 50Hz amp draw will be half of what is listed in charts.

#### ∠ HIGH VOLTAGE LIGHT SYSTEMS

Select from either 250 or 500 watt systems to achieve the lighting effect desired for your Otterbine system. These light systems operate off of 115V in 60Hz, or 230V in 50Hz and are manufactured from stainless steel and brass components protecting them in corrosive environments.

Recommended for our Large Aerating Fountain and Giant Fountain product lines, these systems are ETL & ETL-C approved and can also be used with all 5HP products except High Volume.



High Voltage

Lights (250W)			2	3	4
Junction Box			1	1	1
Amp Draw (Total)*			4.4	6.6	8.8
Lamp Wattage (Total)			500	750	1000
Candlepower (Total Lumens)			10,000	15,000	20,000
Lights (500W)	4	6		8	12
Junction Box	1		2	2	3

Lights (500W)	4	6	8	12
Junction Box	1	2	2	3
Amp Draw (Total)*	17.6	26.4	35.2	52.8
Lamp Wattage (Total)	2000	3000	4000	6000
Candlepower (Total Lumens)	41,800	62,700	83,600	125,400

<sup>\*50</sup>Hz amp draw will be half of what is listed in charts.



#### PAR 64 HIGH VOLTAGE LIGHT SYSTEMS



Including two lights per set, these systems feature 1000W bulbs that are capable of illuminating our most impressive patterns. Manufactured of stainless steel and brass, these light sets operate on 115V and are available for 60Hz markets.

Safety tested and approved by ETL & ETL-C and recommended for our Large Aerating Fountain and Giant Fountain product lines, and are not intended for 5HP High Volumes. Colored lens and sequencing packages are not available for these systems.

Lights (1000W)	2
Amp Draw (Total)*	17.6
Lamp Wattage (Total)	2000
Candlepower (Total Lumens)	38,800

Par 64 High Voltage